

HYFLEX 6X29FI

A high quality flexible crane rope with an independent wire rope core. It is designed to serve as a reliable hoist, boom, or trolley rope in container handlers.

High quality flexible
crane rope

Consistent
performance

Independent wire
rope core




BRUNTON
WIRE ROPES
THE SPECIALIST



HYFLEX 6X29FI

Constructions	Core	Range	Rope grade	MBF
6x29Fi	Steel core	10mm - 60mm	1620 / 1770	63.6 - 2440 kN



Typical applications

Elevator Ropes ▪ Governor Ropes



NOM. ROPE DIA. mm	APPROX. MASS kg/100m	MINIMUM BREAKING FORCE	
		GALVANISED & UNGALVANISED	
		1620 N/mm ²	1770 N/mm ²
		GRADE A kN	GRADE B kN
10	44	63.6	67.7
11.2	55.2	79.8	84.9
12.5	68.8	99.4	106.0
14	86.3	125.0	133.0
16	113.0	163.0	173.0
18	143.0	206.0	219.0
20	176.0	254.0	271.0
22.4	221.0	319.0	340.0
25	275.0	398.0	423.0
28	345.0	499.0	531.0
30	396.0	573.0	609.0
31.5	437.0	631.0	672.0
33.5	494.0	714.0	760.0
35.5	555.0	802.0	853.0
37.5	619.0	895.0	952.0
40	704.0	1020.0	1080.0
42.5	795.0	1150.0	1220.0
45	891.0	1290.0	1370.0
47.5	993.0	1440.0	1530.0
50	1100.0	1590.0	1690.0
53	1240.0	1790.0	1900.0
56	1380.0	2000.0	2120.0
60	1580.0	2290.0	2440.0

Note: Rope Sizes and Breaking Force not shown in the standard table, may be available on request and prior confirmation.



Get in touch with us

Write to us at contact@bsme.uae

To send us a detailed enquiry

[CLICK HERE →](#)

Use our rope selector to find the right rope

[CLICK HERE →](#)

برنتن وایر راپس فز ک ح

BW
Brunton Wire
Ropes FZCo.

P.O. BOX 17491, JEBEL ALI FREE ZONE, DUBAI, UAE

PH.: + 9714 8838755, + 971 50 9537280, + 971 50 177 5929, + 971 50 450 3717

FAX: + 9714 8838152 | E-MAIL: wireropes@bsme-uae.com, sm@bsme-uae.com, bmall@bsme-uae.com

an  **usha martin** Group company